# EDM 2000 MP on BOARD AIR COMPRESSOR TRUCK MOUNTED/TRACK MOUNTED



Safety - Efficiency - Trust



## EDM 2000 MP on board air compressor truck mounted/track mounted

#### **Diesel Engine**

DDC/MTU 12V2000 TA Tier II 850HP@1800 rpm V-Pack Cooler pack 55 degree ambient

#### **Sullair Compressor with Airdrill Clutch**

1350 cfm@500psi

#### **Rotation Head Top Head Drive**

Hollow Floating spindle ID: 70mm – 3 ½" API IF pin thread Two speed, Low/High manual gear change 7700Lbft@188 rpm (Max. Break out torque) 1160Lbft@1250 rpm

#### Mast

Heavy Duty section mast structure Capable of angles from vertical to 45° 2000mm mast dump

#### **Head Traverse**

Driven by one hydraulic cylinder, 2:1 rope system Max speed up cylinder 447mm/sec, rope system 894mm/sec Max speed down cylinder 335mm/sec, rope system 670mm/sec 7.6m stroke with rotation head

#### **Pull Down**

17,500 Lbf

#### Pull Out

60,000 Lbf

#### **Main Hoist**

Mounted on top of mast (Type Braden RW500)

Max pull 55,000 Lbf

Max speed 75m/minute

Failsafe brake mechanism (spring applied, hydraulic release)

9 metre pull for diamond pipe and casing

Load sensing winch motor for optimum operating speed

#### Jib Boom

Actuated by hydraulic cylinder for raise/lower Actuated by hydraulic hourglass worm for left/right Independent winch with lifting capacity of 200kg

#### **Water Pump**

FMC (Bean) W1122BCD 140 LPM@7,000KPa

Powered from rig hydraulic system

#### Rod Break Out

48" Adjustable Stillson wrench hydraulic cylinder mounted for hydraulic break out
Diaspan wrap spanner for N+, H+ and P+ casing

#### **Rod Spinner (Optional)**

Chuck type floating Rod Spinner 2,200Lbft breaking torque Adjustable torque control

#### Jack Leg

Heavy Duty cylinder with pilot check valves Extra large pads for better ground stability

#### **Rod Clamp and Slip Table**

Hydraulic operated, self energising rod clamp Easy to remove jaws Common jaws from 44.5mm to 177.8mm (B+, N+, H+ and P+ casing)

#### Wire Line Winch Mounted on mast pivot plate

Capacity ¼" rope: 2000m Max average pull from full to empty drum 3,680Lbf Max average speed from full to empty drum 7m/sec Automatic rope tracking device

#### **Control Panel**

Easy self explanatory layout
Easy access for basic maintenance and repairs
Fully sealed control panel with all electrical instrumentation

#### **Mud Mixing Circuit**

30 LPM pump independent from all other function, with flow control, and quick release connectors

#### **Hvdraulics**

Danfoss pump & motors, Parker CVG main valve, Danfoss PVG32 auxiliary valves, Sun cartridge

#### **Rod Spin Guard**

Cage off the rotating rods from operator
Hydraulically interlocked with rotation
Reduces rotation speed to 150 rpm when cage is opened

#### Theoretical Rated Depth Capacity Diamond Coring Q Series

Pipe

B - 2800m

N - 2500m

H - 2000m

P - 1200m



## EDM 2000 MP on board air compressor truck mounted/track mounted

#### Theoretical Rated Depth Capacity Reverse Circulation Drilling

4" – Dual Wall RC pipe – 650m 4 ½" – Dual Wall RC pipe – 600m

#### Tilting Rod Bin

Capacity of 28 x 4-1/2" RC

#### **Dimensions**

Platform Width 2,500mm Jack leg centres 6,600mm Mast Length 12,135mm Overall Height 4,300mm

#### Safety Features

- •Guards on all rotating equipment
- ·Anti slip grid mesh on all work platforms
- Hand rails on all work platforms
- •Emergency stops in control cabinet and on both sides of machine
- •Rod spin guard with hydraulic interlock. Reduces rotation to 100 rpm when opened.
- Heat guards on all exhaust manifolds and piping
- •Murphy shut down system which protects the following
- Low engine oil pressure
- •High engine temperature
- Low hydraulic tank oil level
- •24 volt, 100amp alternator to enable high quality additional work lights
- Two certified 10kg fire extinguishers

#### Standard Features

- Easy accessible control panel for general maintenance
- Clear easy to read and self explanatory controls
- Warning horn to alert drill crew
- Central grease point for wireline and top sheave wheels
- •Easy accessible oil drain station for engine, hydraulic tank, FMC pump
- •Remote mounted oil and fuel filter station
- Fully sealed electrical panel
- ·Hydraulic test points on all pumps, motors, and spool banks

- Battery isolation switch
- Fuel tank gauge
- •Clearly labelled oil type and grades on all oil fill points
- ·Level bubbles mounted on platform and mast
- Tool box
- Two additional available spool banks, one with detent, one spring centre for additional mud mixing systems, casing jacks, etc
- •All jaw sets from B+, N+, H+, P+.
- Stillson wrench for hydraulic break out, 48" inch
- •10m of 2 inch suction hose with foot valve and cam lock connectors
- •First 250 and 500 hr service kit
- •Flashing light, and standard mine site lighting
- Mast ladder
- •Rig platform access ladders and steps
- ·Large fully adjustable offsiders platform
- •EDM products are designed with standard imperial materials. All threads are either UNC or UNF. All hydraulic valves bodies, pumps, motors use common SAE O-ring boss adaptors

#### **Additions for RC Drilling Capacity**

- Hammer oiler
- •28 x 4-1/2" drill pipe capacity hydraulic tilting rod bin
- •Hydraulic operated air on/off and vent valves
- •1500psi rated 2" air hose with certified hoses socks on all high pressure air lines
- Drill star bottom swivel assembly
- Drill star top swivel assembly
- Inner tube & deflector box assembly
- •500psi rated 3" sample hose assembly with certified hose socks & hardened Boss hose tails
- •Hydraulic operated adjustable rod kicker operated from foot pedal on drillers platform
- •Hydraulic operated table spanner
- •Rod spin guard assembly with hydraulic interlock
- Slips table assembly
- •1500psi valving for auxiliary compressor & booster connections
- Rod Handler



# EDM 2000 MP on BOARD AIR COMPRESSOR TRUCK MOUNTED/TRACK MOUNTED

#### Warranty

1 Year / 5000 hrs

#### **Optional Features**

- Reverse circulation kit
- •KL Rod loader for RC pipe only
- Additional sealed lockable Tool Box
- Additional work lights
- •Hydraulic boost kit for high altitudes (Prevents hydraulic pump cavitation)
- •Fully silenced, and enclosed deck for quite and cleaner machine
- •6 inch tradesmen vice
- Gas bottle mounts
- Hydraulic welder and generator package
- •1500 hr service kit
- •Remote spare parts kit
- Clients colour choice
- •Fire suppression unit
- Chuck type rod spinner
- •Extendable front jack legs for removing truck or crawler carrier.
- •FMC L11-18SC Disc 65gpm high pressure water pump

#### **Carrier Options**

- •6 x 6 Truck
- •6 x 4 Truck
- Track carrier